

Urethane FLEX Tube

Hydrophobic
Urethanes

DESCRIPTION

Urethane Flex Tube is a very economical solution to prevent water infiltration in cold joints. The **Urethane Flex Tube** is placed on the cold joint during the construction. The cement particles can not penetrate through the walls of the tube, due to its special permeable membrane, but the Urethane resins will migrate through the membrane into the joint. After the concrete structure is completely cured, the construction joints are injected with Urethane resins through the **Urethane Flex Tube**

Hydrophilic
Urethanes

Accessories

PHYSICAL PROPERTIES

Urethane Flex Tube

Tube		
Materials	PET woven around a steel coil	
Diameter	1/2"	(12.50 mm)
Weight	0.046 lbs/foot	(0.07 kg/m)
Length	± 100 ft	(±30 m)
Porosity	35 micron	
Strand		
Diameter	0.5"	(12.70 mm)

Urethane Grout
Technologies

Soil Stabilization

Waterproofing

STORAGE

Store dry areas using original boxes. Keep away from water and humidity.

E-Grout.com

PROCURABLE

Urethane Flex Tube Kit contains 100 ft (30m) **Urethane Flex Tube**, 1 box with 100 attachment clips, 10 Flex Tube connectors and 15 feet of clear reinforced PVC hose.

PRODUCT WARRANTY

The recommendations and suggestions given in this report are made without any representation or warranty, as they are represented for your own investigation and verification. Products discussed are sold without warranty, expressed or implied, in law or fact and upon the condition that purchasers make their own tests to determine the suitability of such products for their particular purposes. Manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. Manufacturers will not be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Users should consider this data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.